



MP-2 (Passive), MP-2L (Active)

FEATURES

- 2 RU chassis enclosed unit
- High quality audio monitoring
- 10 position input select switch
- High quality 3" speaker
- Phoenix compression screw terminals for input connectivity
- Volume control
- Headphone jack, front mounted
- Active or passive versions available
- Optional VU meter for visual monitoring
- Made in the USA

The RCI Custom Products **MP-2** Passive and **MP-2L** Active Rack Mount Audio Monitor Panels offer convenient signal monitoring of multiple signal sources at the head end equipment rack or other remote location.

The MP-2 passive monitor panel monitors up to 10 zones of signal source at 25V or 70V. The MP-2L active monitor panel monitors up to 10 line level signals. The MP-2L active unit is equipped with an AC line cord to plug into any standard 115VAC outlet.

Both units provide compression screw terminal strips for easy input connectivity. Also included on both versions is a high quality 3" speaker for monitoring, a headphone lift jack for discreet monitoring, and output volume control for listening to either the internal speaker or the headphones.

The MP Series monitor panels are available with an optional VU meter. Units require 2 rack spaces for mounting and are 9" deep.

A & E SPECIFICATIONS

Monitor panel shall be RCI Custom Products Model _____ (MP-2, MP-2L) Unit shall be capable of monitoring up to 10 channels or zones. The MP-2 Passive monitor panels shall accept inputs from 25V or 70V audio signals. The MP-2L Active monitor panel shall be capable of accepting audio signals from line level pre-amplified sources. Units shall be equipped with an integrated 3" loudspeaker, speaker volume control and headphone output for discreet monitoring. Rear panel connectivity shall be via Phoenix style screw connectors. Units shall be 3 1/2" tall and fit in a standard 2 RU EIA 19" rack space.